



# Nove 03 Series Architectural LED Downlight



**Base**  
LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K


<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 7W (Reflector beam angle: 15° / 25° / 38° / 55°)</p> <p>LD With DC 36V 200mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-7W-03-F</b> White</p>	<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 10W (Reflector beam angle: 15° / 25° / 38° / 55°)</p> <p>LD With DC 36V 250mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-10W-03-F</b> White</p>	<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 15W (Reflector beam angle: 15° / 25° / 38° / 55°)</p> <p>LD With DC 36V 400mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-15W-03-F</b> White</p>
---	---	---



**Base**  
LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K


<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 15W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 400mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-15W-03-F</b> White</p>	<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 20W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 550mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-20W-03-F</b> White</p>	<p>Base Cut-off angle 55°</p> <p>COB LED(LUMINUS) 25W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 700mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-25W-03-F</b> White</p>
--	--	--



**Adjustable**  
LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 7W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 200mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-7W-03-G</b> White</p>	<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 10W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 250mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-10W-03-G</b> White</p>	<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 15W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 400mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅75mm</p> <p><b>GJNOV-15W-03-G</b> White</p>
---	---	---




**Adjustable**  
LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 15W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 400mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-15W-03-G</b> White</p>	<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 20W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 550mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-20W-03-G</b> White</p>	<p>Adjustable Cut-off angle 55°</p> <p>COB LED(LUMINUS) 25W (Reflector beam angle: 15° / 25° / 38°)</p> <p>LD With DC 36V 700mA LED Driver</p> <p>AC 100V~240V 50/60Hz</p> <p>Ra 90</p> <p>LE* / TE* / 0-10V / Dali</p> <p>∅125mm</p> <p><b>GJNOV-25W-03-G</b> White</p>
--	--	--

# Nove 03 Series Architectural LED Downlight




## Base

LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

Base	Cut-off angle 55°	Base	Cut-off angle 55°	Base	Cut-off angle 55°
COB LED(LUMINUS) 25W (Reflector beam angle: 15° / 25° / 38° )	COB LED(LUMINUS) 30W (Reflector beam angle: 15° / 25° / 38° )	COB LED(LUMINUS) 35W (Reflector beam angle: 15° / 25° / 38° )			
With DC 36V 700mA LED Driver	With DC 36V 800mA LED Driver	With DC 36V 900mA LED Driver			
AC 100V~240V 50/60Hz	AC 100V~240V 50/60Hz	AC 100V~240V 50/60Hz			
<b>Ra</b> 90	<b>Ra</b> 90	<b>Ra</b> 90			
LE* / TE* / 0-10V / Dali	LE* / TE* / 0-10V / Dali	LE* / TE* / 0-10V / Dali			
$\varnothing$ 150mm	$\varnothing$ 150mm	$\varnothing$ 150mm			
<b>GJNOV-25W-03-F</b> White	<b>GJNOV-30W-03-F</b> White	<b>GJNOV-35W-03-F</b> White			

**CE** IP20




## Base

LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

Base	Cut-off angle 55°
COB LED(LUMINUS) 50W (Reflector beam angle: 15° / 25° / 38° )	
With DC 36V 1200mA LED Driver	
AC 100V~240V 50/60Hz	
<b>Ra</b> 90	
LE* / TE* / 0-10V / Dali	
$\varnothing$ 150mm	
<b>GJNOV-50W-03-F</b> White	

**CE** IP20




## Adjustable

LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

Adjustable	Cut-off angle 55°
COB LED(LUMINUS) 50W (Reflector beam angle: 15° / 25° / 38° )	
With DC 36V 1200mA LED Driver	
AC 100V~240V 50/60Hz	
<b>Ra</b> 90	
LE* / TE* / 0-10V / Dali	
$\varnothing$ 150mm	
<b>GJNOV-50W-03-G</b> White	

**CE** IP20



## Adjustable

LED Hotel architectural Series

Lamp Source: CREE / SHARP / BRIDGELUX ..... Color matching: 2700K / 3000K / 3500K / 4000K / 5000K / 6500K

Adjustable	Cut-off angle 55°	Adjustable	Cut-off angle 55°	Adjustable	Cut-off angle 55°
COB LED(LUMINUS) 25W (Reflector beam angle: 15° / 25° / 38° )	COB LED(LUMINUS) 30W (Reflector beam angle: 15° / 25° / 38° )	COB LED(LUMINUS) 35W (Reflector beam angle: 15° / 25° / 38° )			
With DC 36V 700mA LED Driver	With DC 36V 800mA LED Driver	With DC 36V 900mA LED Driver			
AC 100V~240V 50/60Hz	AC 100V~240V 50/60Hz	AC 100V~240V 50/60Hz			
<b>Ra</b> 90	<b>Ra</b> 90	<b>Ra</b> 90			
LE* / TE* / 0-10V / Dali	LE* / TE* / 0-10V / Dali	LE* / TE* / 0-10V / Dali			
$\varnothing$ 150mm	$\varnothing$ 150mm	$\varnothing$ 150mm			
<b>GJNOV-25W-03-G</b> White	<b>GJNOV-30W-03-G</b> White	<b>GJNOV-35W-03-G</b> White			

**CE** IP20

